

MATERIAL SAFETY DATA SHEET

This material is hazardous according to health criteria of Safe Work Australia.

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **MONOTEK® HBE Epoxy Thinner**

Recommended use: Thinner for epoxy paints.

Supplier: MONOTEK Pty Ltd ABN: 54 679 277 840

Street Address: 2 / 25 Jersey Road Bayswater VIC 3153 Australia

Telephone: +613 9720 8777

Emergency Telephone number: (03) 9720 8777 from 8:30 am to 5.00 pm

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word - Danger

Hazard Classifications

Flammable Liquids

- Category 2

Aspiration Hazard

- Category 1

Acute toxicity

- Category 4 Dermal

Skin Corrosion/Irritation

- Category 2

Serious Eye Damage/Irritation

- Category 2A

Acute toxicity

- Category 4 Inhalation

Specific Target Organ Toxicity (Single Exposure)

- Category 3 Narcotic Effects

Toxic to Reproduction

- Category 2

Specific Target Organ Toxicity (Repeated Exposure)

- Category 2

Hazard Statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child .

H373 May cause damage to organs through prolonged or repeated exposure.

Prevention Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.



D P J C O A T I N G S S Y S T E M S

Established in 1977

a business division of- MONOTEK Pty Ltd ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 1 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust, fume, gas, mist, vapours or spray.
P264 Wash hands, face and all exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P330 Rinse mouth.
P331 Do NOT induce vomiting.
P362 Take off contaminated clothing and wash before reuse.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up/ secure.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Classified as dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous good by Road or rail" and the "New Zealand NZS5433: Transport of Dangerous Good on Land"

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Toluene	108-88-3	30-60 % (w/w)
Xylene	1330-20-7	30-60 %
Methyl ethyl ketone	78-93-3	10-30 %
Denatured Ethanol	64-17-5	10-30 %
Ingredients determined to be Non-Hazardous		Balance



D P J C O A T I N G S Y S T E M S

Established in 1977

a business division of - **MONOTEK Pty Ltd** ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 2 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).

For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: 3YE

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.



DPJ COATING SYSTEMS

Established in 1977

a business division of - **MONOTEK Pty Ltd** ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 3 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition.

Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

As published by Safe Work Australia

	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Toluene	50	191	150	574	Sk
Xylene (o-, m-, p- isomers)	80	350	150	655	-
Methyl ethyl ketone	150	445	300	890	-
Ethanol	1000	1880	-	-	-

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

SK Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.



D P J C O A T I N G S S Y S T E M S

Established in 1977

a business division of - **MONOTEK Pty Ltd** ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 4 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National model regulations for the control of workplace hazardous substances (Safe Work Australia)" The ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps.

Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment:

SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing & other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid	Colour:	Clear
Odour:	Solvent	Solubility:	Partly soluble in water
Specific Gravity (20 °C):	0.9	Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	10 KPa	Flash Point (°C):	<23
Flammability Limits (%):	N Av	Auto ignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av	Boiling Point/Range (°C):	78 - 143
pH:	N App	Viscosity:	< 14 cSt @ 40 °C
Total VOC (g/Litre):	900 g/L		
<i>(Typical values only - consult specification sheet)</i>		<i>N Av = Not available, N App = Not applicable</i>	

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.



DPJ COATINGS SYSTEMS

Established in 1977

a business division of - MONOTEK Pty Ltd ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 5 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Skin contact: Contact with skin will result in irritation.

Eye contact: An eye irritant.

Acute toxicity

Inhalation: This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 10 - 20 mg/L

Skin contact: This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 1000 - 2,000 mg/Kg

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as Hazard Category 2A. May cause serious eye irritation. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as Aspiration Hazard Category 1.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

Chronic Toxicity

Mutagenicity / Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as Category 2 Hazard, suspected of damaging fertility or the unborn child

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 2 Hazard. Exposure via inhalation may cause damage to organs through prolonged or repeated exposure.



D P J C O A T I N G S Y S T E M S

Established in 1977

a business division of - **MONOTEK Pty Ltd** ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 6 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bio-accumulative potential: No information available. **Mobility:** No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see Section 8. "Exposure Controls/ Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of dangerous Goods by Road or Rail and the New Zealand NZS5433: Transport of dangerous Goods on Land"



Packing Group: II
Hazchem Code: +3YE
Proper Shipping Name:

UN No: 1263 **Dangerous Goods Class: 3**
Emergency Response Guide No: 14
PAINT RELATED MATERIAL

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT



D P J C O A T I N G S S Y S T E M S

Established in 1977

a business division of - **MONOTEK Pty Ltd** ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 7 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 1263 Dangerous Goods Class: 3
Proper Shipping Name: PAINT RELATED MATERIAL

Packing Group: II

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1263 Dangerous Goods Class: 3
Proper Shipping Name: PAINT RELATED MATERIAL

Packing Group: II

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)
Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

This material/constituent(s) is covered by the following requirements:

All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC) .

HSNO Group Standard: HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard 2006



DPJ COATING SYSTEMS

Established in 1977

a business division of - MONOTEK Pty Ltd ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777 E: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 8 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION

Reason for issue: Update to GHS SDS standard.

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.



D P J C O A T I N G S Y S T E M S

Established in 1977

a business division of - **MONOTEK Pty Ltd**

ABN 54 679 277 840

Victoria:

(Head Office) 2 / 25 Jersey Road, Bayswater. 3153

Phone: (03) 9720 8777

E: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE - Thinners

Issued: 24/10/2024

Page 9 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.