

MATERIAL SAFETY DATA SHEET

Safety Data Sheet

This material is hazardous according to health criteria of Safe Work Australia.

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **MONOTEK® HBE Pack A**

Recommended use: As a floor coating when mixed with other components of the Monotek HBE system.

Supplier: D.P.J. Coating Systems Pty Ltd

ABN: 56 005 509 679

Street Address: 2 / 25 Jersey Road Bayswater VIC 3153 Australia

Telephone: +613 9720 8777

Facsimile: +613 9720 8540

Emergency Telephone number: (03) 9720 8777 from 8:30 am to 5:00 pm

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word



Warning

Hazard Classifications

Skin Corrosion/Irritation	- Category 2
Serious Eye Damage/Eye Irritation	- Category 2A
Skin Sensitization	- Category 1
Long Term Aquatic Hazard	- Category 2

Hazard Statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects

Prevention Precautionary Statements

P261 - Avoid breathing vapour.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves: > 8 hours (breakthrough time): butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL). Wear eye or face protection.



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 1 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

Response Precautionary Statements

P391 - Collect spillage.

P302 + P352 + P362-2 + P363 - IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing. Wash contaminated clothing before reuse.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage Precautionary Statements

Not applicable.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Not subject to ADG Code

Not Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous good by Road or rail" and the "New Zealand NZS5433: Transport of Dangerous Good on Land", (refer section 14).

Dangerous Goods Class: Not applicable,

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)	25068-38-6	60-100 %
Glycidylether of C12-C14 alcohols	68609-97-2	10- 30 %
Bisphenol F epoxy resin	9003-36-5	10- 30 %
Ingredients determined to be Non-Hazardous		Balance



DPJ COATING SYSTEMS Pty Ltd

ABN 56 005 509 679 ACN 005 509 679

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

Phone: (03) 9720 8777 Facsimile: (03) 9720 8540

Toll free - 1800 062 301 (Australia-wide)

Email: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 2 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin Contact:

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact:

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Ingestion:

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel.

If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Notes to physician: No specific treatment. Treat symptomatically. Call medical doctor or poison control centre immediately if large quantities have been ingested.



D P J COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 3 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES

Hazchem Code: 2X

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Specific hazards: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products: Burning produces obnoxious and toxic fumes. Carbon oxides

Special precautions for fire fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire fighting further advice: Not available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental Precautions: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods & materials for containment & cleaning up: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Dangerous Goods Initial Emergency Response Guide No: 47



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 4 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

7. HANDLING AND STORAGE

Handling: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage: Store between the following temperatures: 2 to 40°C. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Storage, class 9 Miscellaneous Dangerous Goods.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

TWA		STEL		NOTICES
ppm	mg/m3	ppm	mg/m3	

None available.

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Sk Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable.

Biological Limit Values: As per the "National model regulations for the control of workplace hazardous substances (Safe Work Australia)" The ingredients in this material do not have a Biological Limit Allocated.



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 5 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals.

They are not a measure of relative toxicity.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL) should be suitable for long term application. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid	Colour: Clear or coloured.	Odour: Mild.
Solubility: Insoluble in water	Specific Gravity (20 °C): 1.10 - 1.34 at 25°C	Vapour Pressure (20 °C): N Av
Relative Vapour Density (air=1): N Av.	Flammability Limits (%): N Av	Melting Point/Range (°C): N Av
Flash Point (°C): Closed cup: >155°C	pH: N App	Total VOC (g/Litre): Nil
Auto ignition Temperature (°C): N Av		
Boiling Point/Range (°C): N Av		
Viscosity: > 14 cSt @ 40 °C		

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Take precautionary measures against electrostatic discharge.

Incompatible materials: Strong acids, strong bases, strong oxidising agents.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Decomposition products may include the following materials: Carbon oxides, Burning produces obnoxious and toxic fumes.

Hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 6 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: No specific data.
Skin contact: Causes skin irritation. May cause an allergic skin reaction.
Ingestion: No specific data.
Eye contact: Causes serious eye irritation.

Acute toxicity

Inhalation: No known significant effects or critical hazards
Skin contact: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Ingestion: No known significant effects or critical hazards.
Corrosion/Irritancy: Eye: Irritating to eyes.
Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a skin sensitiser.
Aspiration hazard: This material has been classified as non-hazardous.
Specific target organ toxicity (single exposure): This material has been classified as non hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.
Carcinogenicity: This material has been classified as non-hazardous.
Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.
Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information available.

Long-term aquatic hazard: This material has been classified as a Category Chronic 2 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or BCF 500 and/or log Kow 4.

Ecotoxicity & Persistence /degradability: No information available.

Bioaccumulative potential: No information available. **Mobility:** No information available.



D P J COATING SYSTEMS Pty Ltd

ABN 56 005 509 679 ACN 005 509 679

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 7 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see Section 8. "Exposure Controls/ Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Australian Special Provision AU01 to the Australian Dangerous Goods Code 7th Edition (incorporating Corrigendum 1) 2011 states – Environmentally Hazardous Substances meeting the descriptions of UN3077 or UN3082 are not subject to this Code when transported by road or rail in;
(a) Packagings that do not incorporate a receptacle exceeding 500 kg (L); or (b) IBCs.

Where not subject to ADG7:

UN number: Not applicable **Proper shipping name:** Not applicable **Class:** Not applicable
Packing group: Not applicable **Hazchem code:** Not applicable

Where subject to ADG7:



UN number: 3082
Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.
(Bisphenol a/f epoxy resin)
Australian Dangerous Goods Class: 9
Packing group: III **Hazchem code:** 2X

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1).

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 3082
Packing Group: III
Dangerous Goods Class: 9

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a/f epoxy resin)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 3082
Packing Group: III
Dangerous Goods Class: 9

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol a/f epoxy resin)



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

www.monotek.com.au

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 8 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.

MATERIAL SAFETY DATA SHEET

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)
Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish
International Convention for the Prevention of Pollution from Ships (MARPOL)
Annex II - Noxious Liquid Substances carried in Bulk
Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

HSNO Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006

16. OTHER INFORMATION

Reason for issue: First Issue

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.



DPJ COATING SYSTEMS Pty Ltd

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

ABN 56 005 509 679 ACN 005 509 679
Phone: (03) 9720 8777 Facsimile: (03) 9720 8540
Toll free - 1800 062 301 (Australia-wide)
Email: admin@dpj.com.au

w w w . m o n o t e k . c o m . a u

Product Name: MONOTEK HBE – Part A

Issued: 24/03/2016

Page 9 of 9

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used each user must, prior to use, assess and control the risks arising from the use of the product.